


K012

Double Metal Cradle Swing

INFORMATION ABOUT PRODUCT

Minimum Space	300x700x317 cm
Impact Protection net	21 m ²
Dimensions	280x158 cm
Overall Height	250 cm
Free falling height	130 cm
Foundations	4 pcs
Availability of spare parts	YES
Product complies with EN 1176	YES
Age range	1,5-4
Amount of users	2



MATERIALS

- Top Axle: Hot Dip Galvanized metal circular cross section cross bar with large steel end-plates attached
- Footings: Hot Dip Galvanized and powder coated Steel tubes
- Decorative Panels: HPL (EXT)
- Chains: Hot Dip Galvanized (plain) or Stainless Steel (304 / 316L) / Ø6mm / According to DIN 766
- Swing joints, Stainless steel heavy duty with nylon bearings
- Swing seat (normal): Injection molded TPE (thermoplastic elastomer) reinforced with an aluminum insert plate
- Swing seat (infant): Injection molded TPE (thermoplastic elastomer) reinforced with an aluminum insert plate. Protective apparatus made in the same manner.
- Nest swing 'rosette': Hot Dip Galvanized steel ring wrapped with steel core rope braided with polypropylene. Seat made of steel-rope chain-link mat. The suspension ropes are made with steel core rope braided with polypropylene ending with a stainless-steel chain on the top end to adjust the suspension length. The shackles are made in high-quality stainless steel. All of the clip rings are made in aluminum.
- Fasteners: Electroplated coated or Stainless Steel (304 / 316L)
- Ground Anchors: Hot Dip Galvanized steel



Please note that the above list of materials concerns the articles of the whole series. Therefore, some of them are not used in the described article.